

Vandal-proof Housing

14-in. Housing with Optional IR Illumination



- Aluminum Construction (casing)
- Optional Built-in IR Illumination and Heater
- Designed for Reliability and Aesthetics
- IP67 Ingress Protection and IK10 Impact Resistance

Technical Specifications

Environmental

	PFH610V	PFH610V-IR
Operating Temperature	−30 °C to 60 °C (−22 °F to 140 °F)	−40 °C to 60 °C (−40 °F to 140 °F)
Humidity	< 90%	
Ingress Protection	IP67	
Impact Resistance	IK10	

Electrical

Power Supply	12 VDC or 24 VAC	24 VDC or 24 VAC, 5 A
Power Consumption	N/A	67 W
IR Distance	N/A	100 m (328.08 ft)

Construction


Material	Case: Aluminum Other: PC Plastic	
Color	White	
Outer Dimensions (L x W x H)	404.0 mm x 164.0 mm x 132.0 mm (15.91 in. x 6.46 in. x 5.20 in.)	
Inner Dimensions (L x W x H)	215.0 mm x 90.0 mm x 83.0 mm (8.46 in. x 3.54 in. x 3.27 in.)	
Weight	2.50 kg (5.51 lb)	3.0 kg (6.61 lb)
Cortifications		

Certifications

CE, FCC, ICES	CE, FCC, UL, EAC, ICES
CE, FCC, ICES	CE, FCC, UL, EAC, ICES

Ordering Information			
Туре	Part Number	Description	
Vandal-proof Housing	PFH610V	14-in. Housing, IP67, IK10	
	PFH610V-IR	14-in. Housing, IP67, IK10, IR, Built-in Heater	
Accessory, optional	PFB604W	Wall-mount Bracket	
Package Contents			
DH-PFH610V	1	Vandal-proof Housing	
	2	M20 Waterproof Joints	
	2	1/4/20x8 Screws	
	1	S5.0 Wrench	
DH-PFH610V-IR	1	Vandal-proof Housing	
	2	M20 Waterproof Joints	
	2	1/4/20x8 Screws	
	1	S5.0 Wrench	
	1	Connection Cord (to connect camera to IR driver board)	

50.0 - 50.0 - 2-M20 XP1.5



Dimensions (mm)

