

# DH-PFL16-L12M-A

12MP 1.1" F1.4 16 mm Fixed-focal Lens (Manual Iris)



- 1.1" image sensor with high compatibility for ITC cameras.
- IR correction ensures 24 hours real-time monitoring.
- Standard C mount for easy installation and strong compatibility.
- · ROHS standard.

Port

Storage Temperature

Storage Humidity

#### **Technical Specification** Performance 1.1" Image Sensor Size 16 mm Focal Length Lens Pixel 12MP Aperture F1.4 ± 10% IR Light Yes 10.3° CRA Total Optical Length 96.6 mm ± 0.5 mm (in air) Flange Back Focal Length 17.52 mm ± 0.2 mm (in air) Mechanical Back Focal 11.74 mm ± 0.2 mm (in air) Length Field of View 61.3° × 50.3° × 37° (D × H × V) Distortion -2.35% Minimum Object Distance 0.3 m (0.98 ft) (MOD) Control Mode Fixed Zoom Focus Control Manual

Manual

Iris Control

#### Port Type C mount Structure **Product Dimensions** Ф48 mm x 84.25 mm Black Appearance Color Casing Metal Net Weight $0.356 \text{ kg} \pm 0.005 \text{ kg} (0.78 \text{ lb} \pm 0.01 \text{ lb})$ **Gross Weight** $0.408 \text{ kg} \pm 0.010 \text{ kg} (0.90 \text{ lb} \pm 0.02 \text{ lb})$ 124 mm × 82 mm × 89 mm (4.88" × 3.23" × 3.50") **Packaging Dimensions** Environment **Operating Temperature** -30°C to +70°C (-22°F to +158°F) Operating Humidity 95% (RH)

-30°C to +70°C (-22°F to +158°F)

≤ 95% (RH)

## Lens Series | DH-PFL16-L12M-A

Ordering Information		
Туре	Part Number	Description
HD Fixed-focal Lens	DH-PFL16-L12M-A	Dahua 12MP 1.1" F1.4 16 mm Fixed-focal Lens (Manual Iris)
Accessory		Desiccant

### Dimensions (mm[inch])

